Safety Equipment Requirements		
Note: Organizing Authorities may add or delete items based on the conditions of their specific races.		
Effective Date: March 1, 2023, version 2023.0 valid through December 31, 2024		
	Overall	
•	Nearshore: Races primarily sailed during the day, close to shore, in relatively protected	
1.0.3 Definition	waters.	
1.0.5 Delimition	waters.	
	The Safety Equipment Requirements establish uniform minimum equipment and training	
	standards for a variety of boats racing in differing conditions. These regulations do not replace,	
	but rather supplement, the requirements of applicable local or national authority for boating, the	
1.1	Racing Rules of Sailing, the rules of Class Associations and any applicable rating rules.	
1.1	The safety of a boat and her crew is the sole and inescapable responsibility of the "person in	
	charge", as per RRS 46, who shall ensure that the boat is seaworthy and manned by an	
	experienced crew with sufficient ability and experience to face bad weather. S/he shall be	
	satisfied as to the soundness of hull, spars, rigging, sails and all gear. S/he shall ensure that all	
1.2	safety equipment is at all times properly maintained and safely stowed and that the crew knows	
Responsibility	where it is kept and how it is to be used.	
responsibility	Should there be an incident during a race the Organizing Authority or US Sailing may conduct	
	an investigation to determine the facts of the incident and provide recommendations. By	
1.2.1	participating in a race conducted under the SER, the person in charge, each competitor and	
Responsibility,	boat owner agrees to reasonably cooperate with the organizing authority and US Sailing in the	
Investigations	development of an independent incident report.	
investigations	A boat may be inspected at any time by an equipment inspector or measurer appointed for the	
	event. If she does not comply with these regulations, her entry may be rejected or she will be	
	subject to a protest filed by the RC. A Violation of the Safety Equipment Requirements may	
1.3 Inspections	result in a penalty other than disqualification.	
THE INTERCENCTION	All equipment required shall function properly, be regularly checked, cleaned and serviced, and	
	be of a type, size and capacity suitable for the intended use and size of the boat and the size of	
1.4 Equipment	the crew. This equipment shall be readily accessible while underway and, when not in use,	
and Knowledge	stored in such a way that deterioration is minimized.	
1.5 Secure	A boat's heavy items such as batteries, stoves, toolboxes, anchors, chain and internal ballast	
Storage	shall be secured.	
	A boat's hull, including, deck, coach roof, windows, hatches and all other parts, shall form an	
1.7 Watertight	integral watertight unit, and any openings in it shall be capable of being immediately secured to	
Integrity	maintain this integrity.	
	Hull and Structure	
	A boat with moveable or variable ballast (water or canting keel) shall comply with the	
2.2.3 Stability	requirements of Appendix K.	
ZiZio Gtability	точанотного от търъпажта	
2.5.3 Dewatering		
pumps	A boat shall have a manual bilge pump of at least a 10 GPM (37.8 liter per minute) capacity.	
	Safety Equipment	
<u></u>	Each crewmember shall have a life jacket intended for small boat sailing or other active	
	boating. Each such life jacket shall be USCG, ISO, or applicable government approved or shall	
3.1.3 Lifejackets	meet the ocean requirement of 3.1.1.	
J. 1.0 Eliojaokoto	A boat racing between sunset and sunrise shall carry navigation lights that meet U. S. Coast	
3.3.1 Navigation	Guard or applicable government requirements mounted so that they will not be obscured by the	
Lights	sails nor be located below deck level.	
3.4 Fire	A boat shall carry fire extinguisher(s) that meets U.S. Coast Guard or applicable government	
Extinguishers	requirements, when applicable.	
3.5 Sound		
Producing	A boat shall carry sound-making devices that meets U.S. Coast Guard or applicable	
Equipment	government requirements, when applicable.	
_4a.bor	gotomment regulations, mon applicable.	

	A boat shall carry U.S. Coast Guard (or applicable government entity) flares meeting day-night
3.6.6 Flares	requirements not older than the expiration date.
	A boat shall have a throwing sock-type heaving line of 50' (15m) or greater of floating
3.7.3 Throw Line	polypropylene line readily accessible to the cockpit.
	A boat shall carry a Coast Guard or applicable government approved "throwable device". If the
3.7.4 Throwable	device carried under 3.7.1 or 3.7.2 satisfies this requirement, then no additional device is
Device	needed.
3.8.3 VHF	A boat shall have a VHF radio which may be fixed or handheld.
	A boat shall have a permanently mounted magnetic compass independent of the boat's
3.19.1 Compass	electrical system suitable for steering at sea.
	A boat shall carry one anchor, meeting the anchor manufacturer's recommendations based on
3.23 Anchor	the yacht's size, with a suitable combination of chain and line.
3.24.3	A boat shall carry at least two watertight flashlights with spare batteries in addition to the
Flashlights	requirement of 3.24.1.
	A boat shall carry a first aid kit and first aid manual suitable for the likely conditions of the
3.25 Medical Kits	passage and the number of crew aboard.
	A boat shall carry one sturdy bucket of at least two gallons (8 liters) capacity with lanyards
3.27.2 Bucket	attached.
4	Skills
	Annually, two-thirds of the boat's racing crew shall practice man-overboard procedures
4.2 Man	appropriate for the boat's size and speed. The practice shall consist of marking and returning to
Overboard	a position on the water, and demonstrating a method of hoisting a crewmember back on deck,
Practice	or other consistent means of reboarding the crewmember.
	As required in 1.2 above the person in charge shall ensure that all crew members know where
	all emergency equipment is located and how to operate the equipment. In addition, the person
4.4 Crew	in charge and crew should discuss how to handle various emergency situations including Crew
Training	Overboard, Grounding, Loss of steering, Flooding, Fire, Dismasting, and Abandon Ship.
	Lifejackets as described in 3.1.1 – 3.1.3 should be worn by all crew on deck in any conditions
4.6 Crew	where recovery may be difficult. It is recommended that lifejackets be worn by all crew on deck
Training	unless the person in charge has indicated that they may be set aside.